



Chicago Pneumatic



CPG 70

People. Passion. Performance.



Over 100 years of experience

Since 1901 the Chicago Pneumatic name has represented high-performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, generators, accessories and workshop equipment, please visit www.cp.com.

Since 1901 the Chicago Pneumatic name has represented high performance tools and equipment designed for an extensive range of applications. Today, Chicago Pneumatic has a global reach, with local customer centers around the world. Chicago Pneumatic tools, air compressors and generators are tailored to the needs of the industrial, vehicle service, and construction markets. Every day we develop and manufacture new products that are meant to meet your demands not only today, but tomorrow as well.

To learn more about our extensive range of tools, hydraulic attachments, industrial and portable compressors, accessories and workshop equipment, please visit www.cp.com.

Standard Features

- Reliable John Deere engine and Stamford alternator
- 49.2 hour run time at 75% load with integrated 170 gallon in-frame fuel tank
- Environmentally friendly 110% fluid containment frame
- Solid-state digital controller with easy-to-read analog gauges
- Very quiet 67 dB(A)
- Electronic governor for increased voltage stability (0.25%)
- Remote start connections

Options

- Skid-mounted
- Battery charger
- Coolant heater
- Spare tire
- Tool box
- Rear stabilizer jacks
- External fuel connections

Technical Data

Model	CPG 70
Rated Standby Power	62 kW / 78 kVA
Rated Prime Power	56 Kw / 70 kVA
Voltage Selections - 1Ø	120/240
Voltage Selections - 3Ø	208/240/480
Amperage Capacity @ 120 volts 1Ø	2 x 180
Amperage Capacity @ 240 volts 1Ø	180
Amperage Capacity @ 208 volts 3Ø	195
Amperage Capacity @ 240 volts 3Ø	168
Amperage Capacity @ 480 volts 3Ø	84
Sound Pressure Level @ 23 feet @ 75% load	67 dB(A)
Fuel Tank Capacity	170 gal.
Fuel Consumption At 75% Load	3.4 gal/hr
Fuel Autonomy At 75% Load	49.2 hr

Engine	John Deere
Model number	4045TF285
Rated Speed	1800 rpm
Emission Compliance	EPA Tier III
Rated Output	99 HP @ 1800 rpm
Coolant	Water / Glycol
Cylinders	4
Displacement	4.5 L
Engine Control	Electronic

Alternator	Stamford
Model	UCI 224 E
Degree Of Protection / Insulation Class	IP23 / H

Convenience Receptacles	
20 amp - 125 volt GFCI duplex	2
50 amp - 125 / 250 volt twist lock	2

Dimensions (LxWxH) & Weight	
Dimensions, mounted on skid	112 x 44 x 67 in
Weight, wet, mounted on Skid	5,310 lbs
Dimensions, mounted on trailer	176 x 78 x 80 in
Weight, wet, mounted on Trailer	6,560 lbs

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.